

View Online at <https://aerobasegroup.com/nsn/5930-01-283-9111>

Inside Diameter:

0.250 inches single connection

Overall Length:

3.812 inches

Overall Height:

8.593 inches

Overall Width:

3.656 inches

Body Height:

7.562 inches

Unthreaded Mounting Hole Diameter:

0.203 inches

Longest Horizontal Distance Between Mounting Centers:

3.000 inches

Longest Vertical Distance Between Mounting Centers:

6.250 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

5.0 amperes resistive load first voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+0.00/+250.00 actuation point pounds per square inch and +0.00/+250.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal actuation point screw and internal deactuation point screw

Contact Voltage Rating In Volts:

600.0 dc at sea level second voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Nptf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0