NSN 5930-01-284-5662

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-284-5662

| view Offiline at https://aerobasegroup.com/histi/3930-01-204-3002 |
|--|
| Body Style: |
| Bushing mounted |
| Overall Length: |
| Between 1.734 inches and 1.766 inches |
| Overall Height: |
| Between 0.922 inches and 0.954 inches |
| Overall Width: |
| Between 0.922 inches and 0.954 inches |
| Body Diameter: |
| Between 0.922 inches and 0.954 inches |
| Bushing Length: |
| Between 0.484 inches and 0.516 inches |
| Body Length: |
| Between 0.374 inches and 0.468 inches |
| Case Material: |
| Metal |
| Actuator Diameter: |
| Between 0.859 inches and 0.891 inches |
| Actuator Height: |
| Between 0.375 inches and 0.516 inches |
| Actuator Color: |
| Black single actuator |
| Maximum Voltage Rating In Volts: |
| 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Features Provided: |
| Rfi shielding |
| Thready Qty Per Inch (tpi): |
| 24 |
| Thread Size: |
| 0.625 inches |
| Nonpile-up Contact Arrangement: |
| 1 two circuit, double break/double make, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 10.000 amperes resistive dc and 5.000 amperes inductive dc |
| Thread Series Designator: |
| Unef |
| Terminal Type And Quantity: |
| 4.4-1 |

4 tab w/screw

NSN 5930-01-284-5662

Push Switch - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0