# NSN 5930-01-284-6278

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-284-6278

### **Thread Class:**

2a single mounting facility

### Thread Length:

0.437 inches single mounting facility

### **Overall Length:**

2.937 inches

#### First Flat Length:

0.250 inches single actuator

#### Flat Height:

0.215 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.874 inches single actuator

#### **Overall Diameter:**

1.170 inches

#### Individual Section Quantity:

4

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

2 each section front

#### Throw Quantity:

2 each section front

#### **Mounting Method:**

Threaded bushing w/panel seal single mounting facility

#### Thready Qty Per Inch (tpi):

32 single mounting facility

#### Thread Size:

0.375 inches single mounting facility

#### Contact Voltage Rating In Volts:

115.0 ac at sea level

#### Switch Actuator Indexing Position Quantity:

2 single actuator

#### Shaft Type:

Round, flatted single actuator

#### **Terminal Type:**

Tab, solder lug

#### **Contact Switching Action:**

Breaks before makes each section front

## Switch Actuator Positioning Increment:

90.0 degrees single actuator

# NSN 5930-01-284-6278

Rotary Switch - Page 2 of 2



**Contact Load Current Rating:** 

5.0 amperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0