

View Online at <https://aerobasegroup.com/nsn/5930-01-285-0421>

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

1.260 inches

Overall Height:

0.500 inches

Body Diameter:

0.640 centimeters

Mounting Slot Width:

0.147 inches

Body Height:

0.431 inches

Unthreaded Mounting Hole Diameter:

0.147 inches

Distance Between Mounting Facility Centers:

0.944 inches

Temperature Sensing Element Type:

Internal sensor

Mounting Method:

Bracket and slot and unthreaded hole

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Terminal Type:

Quick disconnect, male

Contact Load Current Rating:

2.0 amperes resistive load second voltage and 1.0 amperes inductive load second voltage and 0.5 amperes lamp load second voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

121.00 actuation point degrees fahrenheit and 129.00 actuation point degrees fahrenheit and 106.00 deactuation point degrees fahrenheit and 114.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Disc w/flange

Test Data Document:

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-s-24236/24 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0