# NSN 5930-01-285-5533

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-285-5533

## Inside Diameter:

0.375 inches single connection

## **Overall Length:**

3.470 inches

# **Overall Height:**

6.940 inches

## Overall Width:

2.660 inches

## **Body Height:**

3.470 inches

## Unthreaded Mounting Hole Diameter:

## 0.280 inches

Longest Horizontal Distance Between Mounting Centers:

## 2.720 inches

# Longest Vertical Distance Between Mounting Centers:

## 2.720 inches

Pressure Switch Type:

Differential

### **Operating Tempurature Rating:**

Between -30.0 degrees celsius and 85.0 degrees celsius

#### **Mounting Method:**

Inlet connection and unthreaded hole

## Features Provided:

Electrical access port

#### Thready Qty Per Inch (tpi):

18 single pressure connection

#### **Contact Action Stimulus:**

Increase

Thread Size:

0.375 inches single pressure connection

## Mounting Facility Pattern:

Two position diagonal

## Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

## Terminal Type:

Screw

## Contact Load Current Rating:

 $0.25 \ \text{amperes}$  resistive load third voltage and  $0.25 \ \text{amperes}$  inductive load third voltage

## Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

## Contact Adjustment Range:

+135.00/+1000.00 actuation point pounds per square inch and +25.00/+225.00 deactuation point pounds per square inch

# NSN 5930-01-285-5533

Pressure Switch - Page 2 of 2



Contact Adjustment Type:

External actuation point screw

**Contact Voltage Rating In Volts:** 

600.00 ac at sea level second voltage

Pressure Connector Type:

Swivel nut, flareless, threaded internal single connection

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A048b0