

View Online at <https://aerobasegroup.com/nsn/5930-01-285-5535>

**Body Style:**

Bushing mounted

**Overall Length:**

Between 2.450 inches and 2.570 inches

**Overall Height:**

Between 0.720 inches and 0.780 inches

**Overall Width:**

Between 0.720 inches and 0.780 inches

**Body Diameter:**

Between 0.720 inches and 0.780 inches

**Bushing Length:**

Between 0.410 inches and 0.470 inches

**Body Length:**

Between 0.890 inches and 1.070 inches

**Case Material:**

Metal

**Actuator Length:**

Between 0.710 inches and 0.770 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

Between 0.810 inches and 0.870 inches

**Actuator Width:**

Between 0.710 inches and 0.770 inches

**Actuator Color:**

Red single actuator

**Illuminated Actuator Color:**

Red single actuator

**Actuator Inscription:**

Emer squib single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 30.0 dc

**Inclosure Type:**

Fully enclosed

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.562 inches

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive dc and 1.000 amperes inductive dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac

**Special Features:**

Single switch unit four pole single throw two normally open and two normally closed contacts momentary action

**Thread Series Designator:**

Un

**Terminal Type And Quantity:**

10 tab, solder lug

**Specification Data:**

53711-6218173 manufacturers source control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0