

View Online at <https://aerobasegroup.com/nsn/5930-01-285-5541>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Fungus resistant and salt spray resistant

Overall Length:

Between 2.900 inches and 3.020 inches

Overall Height:

Between 0.720 inches and 0.780 inches

Overall Width:

Between 0.720 inches and 0.780 inches

Body Diameter:

Between 0.720 inches and 0.780 inches

Bushing Length:

Between 0.410 inches and 0.470 inches

Body Length:

Between 1.340 inches and 1.520 inches

Case Material:

Metal

Actuator Length:

Between 0.710 inches and 0.770 inches

Actuator Style:

Rectangular

Actuator Height:

Between 0.810 inches and 0.870 inches

Actuator Width:

Between 0.710 inches and 0.770 inches

Actuator Color:

Green single actuator

Illuminated Actuator Color:

Green single actuator

Actuator Inscription:

Tube 2 single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Holding solenoid

Thready Qty Per Inch (tpi):

32

Thread Size:

0.562 inches

Nonpile-up Contact Arrangement:

6 pole, single throw, double make, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 0.500 amperes inductive dc and 2.000 amperes resistive ac and 0.500 amperes inductive ac

Thread Series Designator:

Un

Terminal Type And Quantity:

14 tab, solder lug and 2 wire lead

Specification Data:

53711-6218173 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0