

View Online at <https://aerobasegroup.com/nsn/5930-01-285-6659>

Thread Class:

2a single mounting facility

Thread Length:

0.410 inches single mounting facility and 0.470 inches single mounting facility

Overall Length:

2.050 inches

First Flat Length:

0.248 inches single actuator and 0.252 inches single actuator

Flat Height:

0.205 inches single actuator and 0.215 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.252 inches single actuator

Shaft Length:

0.350 inches single actuator and 0.410 inches single actuator

Overall Diameter:

1.036 inches

Individual Section Quantity:

1

Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section front

Throw Quantity:

6 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

2 single section

Switch Actuator Indexing Position Quantity:

6 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0