

View Online at <https://aerobasegroup.com/nsn/5930-01-285-6663>

Thread Class:

2a

Body Style:

Bushing mount

Bushing Length:

0.380 inches

Body Length:

Between 0.770 inches and 0.850 inches

Body Width:

Between 1.010 inches and 1.090 inches

Body Height:

0.820 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.225 inches

Actuator Height:

0.800 inches

Actuator Position-action Relationship:

Center position maintained and left position momentary and right position momentary

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

End Application:

5845-01-216-9261

Mounting Surface To Terminal End Distance:

0.920 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac

Special Features:

Includes panel seal boot

Thread Series Designator:

Unf

Terminal Type And Quantity:

12 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0