NSN 5930-01-286-1565

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-286-1565
Inside Diameter:
0.438 inches single connection
Overall Length:
5.188 inches
Overall Height:
5.312 inches
Overall Width:
2.812 inches
Body Height:
2.750 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
Shortest Horizontal Distance Between Mounting Centers:
0.656 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
Pressure Switch Type:
Gage
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Decrease
Proof Pressure:
160.00 pounds per square inch gage
Thread Size:
0.438 inches single pressure connection
Mounting Facility Pattern:
Isosceles triangle
Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

9.6 amperes inductive load third voltage

Contact Adjustability:

Deactuation point adjustable

Contact Adjustment Range:

+5.00/+75.00 deactuation point pounds per square inch gage

NSN 5930-01-286-1565Pressure Switch - Page 2 of 2



Contact Adjustment Type:
External deactuation point screw
Contact Voltage Rating In Volts:
550.0 dc at sea level fourth voltage
Pressure Connector Type:
Swivel nut, flareless, threaded internal single connection
Media For Which Designed:
Gas or liquid
Precious Material And Location:
Contact surfaces silver
Precious Material:
Silver
Style Designator:
Rectangular
Thread Series Designator:
Npt single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A048b0