NSN 5930-01-286-2161

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-286-2161

Inside Diameter: 0.250 inches single connection **Hazardous Locations/environmental Protection:** Corrosion resistant **Overall Length:** 3.600 inches **Overall Height:** 3.180 inches **Overall Width:** 2.240 inches **Body Height:** 2.230 inches **End Application:** 5985-01-274-8934 **Pressure Switch Type:** Differential **Mounting Method:** Inlet connection **Features Provided:** Electrical access port Thready Qty Per Inch (tpi): 18 single pressure connection **Contact Action Stimulus:** Increase Thread Size: 0.250 inches single pressure connection **Nonpile-up Contact Arrangement:** 2 pole, double throw, one position momentary **Terminal Type:** Screw **Contact Load Current Rating:** 9.7 amperes resistive load second voltage **Contact Adjustability:** Actuation point adjustable and deactuation point adjustable **Contact Adjustment Range:** +80.00/+100.00 actuation point pounds per square inch and +80.00/+100.00 deactuation point pounds per square inch **Contact Adjustment Type:** Internal actuation point screw and external deactuation point screw **Contact Voltage Rating In Volts:**

Pressure Connector Type:

Plain, threaded internal single connection

230.0 ac at sea level second voltage

NSN 5930-01-286-2161

Pressure Switch - Page 2 of 2



Media For Which Designed:
Gas or liquid
Precious Material And Location:
Contact surfaces silver
Precious Material:
Silver
Style Designator:
Rectangular
Thread Series Designator:
Nptf single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A048b0