

View Online at <https://aerobasegroup.com/nsn/5930-01-286-2163>

Hazardous Locations/environmental Protection:

Salt spray resistant and vibration resistant

Overall Length:

1.250 inches

Overall Height:

0.688 inches

Overall Width:

0.375 inches

Mounting Slot Width:

0.125 inches

Body Length:

0.750 inches

Body Width:

0.316 inches

Body Height:

0.453 inches

Distance Between Mounting Facility Centers:

1.000 inches

Temperature Sensing Element Type:

Internal sensor

Mounting Method:

Bracket and slot

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

1.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

+50.00/+105.00 actuation point degrees celsius

Contact Adjustment Type:

External actuation point screw

Contact Stimulus Rating:

56.00 actuation point degrees celsius

Contact Voltage Rating In Volts:

32.0 dc at sea level second voltage

Special Features:

Adjustment screw is sealed with an organic cement

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0