

View Online at <https://aerobasegroup.com/nsn/5930-01-286-2163>

**Hazardous Locations/environmental Protection:**

Salt spray resistant and vibration resistant

**Overall Length:**

1.250 inches

**Overall Height:**

0.688 inches

**Overall Width:**

0.375 inches

**Mounting Slot Width:**

0.125 inches

**Body Length:**

0.750 inches

**Body Width:**

0.316 inches

**Body Height:**

0.453 inches

**Distance Between Mounting Facility Centers:**

1.000 inches

**Temperature Sensing Element Type:**

Internal sensor

**Mounting Method:**

Bracket and slot

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

1.0 amperes resistive load second voltage

**Contact Adjustability:**

Actuation point adjustable, preset

**Contact Adjustment Range:**

+50.00/+105.00 actuation point degrees celsius

**Contact Adjustment Type:**

External actuation point screw

**Contact Stimulus Rating:**

56.00 actuation point degrees celsius

**Contact Voltage Rating In Volts:**

32.0 dc at sea level second voltage

**Special Features:**

Adjustment screw is sealed with an organic cement

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular w/bracket

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiq:**

A048b0