NSN 5930-01-286-7250

Rotary Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-286-7250

Hazardous Locations/environmental Protection:
Dripproof Overall Longth:
Overall Length:
9.500 inches
Overall Height:
8.000 inches
Overall Width:
8.000 inches
Unthreaded Mounting Hole Diameter:
0.281 inches single mounting facility
Individual Section Quantity:
4
Longest Horizontal Distance Between Mounting Centers:
8.750 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
4.000 inches single mounting facility
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob and legend plate and metallic inclosure and cam actuated
Contact Voltage Rating In Volts:
600.0 highest dc voltage rating at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Cam Actuated Switch Contact Arrangement:
1 pole, single throw, double make, both positions maintained each switch each section in-line
Switch Actuator Indexing Position Quantity:
2 single actuator
Contact Load Current Rating:
6.0 amperes resistive load lowest ac voltage rating at sea level
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A052b0