

View Online at <https://aerobasegroup.com/nsn/5930-01-286-8038>

Thread Class:

2a all threaded stud

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

3.375 inches

Overall Height:

7.582 inches

Overall Width:

4.500 inches

Body Height:

4.375 inches

Capillary Tube Length:

72.000 inches

Bulb Length:

4.125 inches

Bulb Diameter:

0.375 inches

Longest Horizontal Distance Between Mounting Centers:

3.375 inches

Longest Vertical Distance Between Mounting Centers:

3.375 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Threaded stud

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

24 all threaded stud

Contact Action Stimulus:

Increase

Thread Size:

0.190 inches all threaded stud

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

500.0 milliamperes inductive load third voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+50.00/+150.00 actuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point screw

Contact Voltage Rating In Volts:

480.0 ac at sea level second voltage

Frequency In Hertz:

60.0 second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Unc all threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0