## NSN 5930-01-286-8042

Push Switch - Page 1 of 2

2a

**Body Style:** 

Bushing mounted



View Online at https://aerobasegroup.com/nsn/5930-01-286-8042

Thread Class:

1.360 inches Overall Height: 0.875 inches Overall Width: 0.875 inches Body Diameter: 0.500 inches Bushing Length: 0.500 inches Bushing Length: 0.501 inches Body Length: 0.516 inches Case Material: Metal Actuator Diameter: 0.375 inches Actuator Height: 0.250 inches Actuator Height: 0.250 inches Actuator Golor: Black single actuator Maximum Voltage Rating In Volts: 30.0 dc Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Features Provided: Rfi shielding Thready Qty Per Inch (tpi): 24 Thread Size: 0.625 inches Nonpile-up Contact Arrangement: 2 two circuit, double break/double make, one position momentary single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc Thread Series Designator: Unef	Overall Length:
Overall Width: 0.875 inches  Body Diameter: 0.500 inches  Bushing Length: 0.500 inches  Body Length: 0.516 inches  Case Material: Metal  Actuator Diameter: 0.375 inches  Actuator Height: 0.250 inches  Actuator Height: 0.250 inches  Actuator Color: Black single actuator  Maximum Voltage Rating In Volts: 30.0 dc  Inclosure Type: Fully enclosed  Mounting Method: Threaded bushing  Features Provided: Rfi shielding  Thready Qty Per Inch (tpi): 24  Thread Size: 0.625 inches  Nonpile-up Contact Arrangement: 2 two circuit, double break/double make, one position momentary single switch unit  Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc  Thread Series Designator:	1.360 inches
Overall Width:  0.875 inches  Body Diameter:  0.500 inches  Bushing Length:  0.500 inches  Body Length:  0.516 inches  Case Material:  Metal  Actuator Diameter:  0.375 inches  Actuator Height:  0.250 inches  Actuator Color:  Black single actuator  Maximum Voltage Rating In Volts:  30.0 dc  Inclosure Type:  Fully enclosed  Mounting Method:  Threaded bushing  Features Provided:  Rfi shielding  Thready Qty Per Inch (tpi):  24  Thread Size:  0.625 inches  Nonpile-up Contact Arrangement:  2 two circuit, double break/double make, one position momentary single switch unit  Cotact Load Current Rating At Maximum Rated Voltage:  5.000 amperes resistive dc  Thread Series Designator:	Overall Height:
Body Diameter: 0.500 inches Bushing Length: 0.500 inches Body Length: 0.516 inches Case Material: Metal Actuator Diameter: 0.375 inches Actuator Height: 0.250 inches Actuator Color: Black single actuator Maximum Voltage Rating In Volts: 30.0 dc Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Features Provided: Rfi shielding Thready Qty Per Inch (tpi): 24 Thread Size: 0.625 inches Nonpile-up Contact Arrangement: 2 two circuit, double break/double make, one position momentary single switch unit Cotact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc Thread Series Designator:	0.875 inches
Body Diameter:  0.500 inches  Bushing Length:  0.500 inches  Body Length:  0.516 inches  Case Material:  Metal  Actuator Diameter:  0.375 inches  Actuator Height:  0.250 inches  Actuator Color:  Black single actuator  Maximum Voltage Rating In Volts:  30.0 dc  Inclosure Type:  Fully enclosed  Mounting Method:  Threaded bushing  Features Provided:  Rfi shielding  Thready Qty Per Inch (tpi):  24  Thread Size:  0.625 inches  Nonpile-up Contact Arrangement:  2 two circuit, double break/double make, one position momentary single switch unit  Contact Load Current Rating At Maximum Rated Voltage:  5.000 amperes resistive dc  Thread Series Designator:	Overall Width:
Bushing Length: 0.500 inches Body Length: 0.516 inches Case Material: Metal Actuator Diameter: 0.375 inches Actuator Height: 0.250 inches Actuator Color: Black single actuator Maximum Voltage Rating In Volts: 30.0 dc Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Features Provided: Rif shielding Thready Qty Per Inch (tpi): 24 Thread Size: 0.625 inches Nonpile-up Contact Arrangement: 2 two circuit, double break/double make, one position momentary single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc Thread Series Designator:	0.875 inches
Bushing Length: 0.500 inches Body Length: 0.516 inches Case Material: Metal Actuator Diameter: 0.375 inches Actuator Height: 0.250 inches Actuator Color: Black single actuator Maximum Voltage Rating In Volts: 30.0 dc Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Features Provided: Rfi shielding Thready Qty Per Inch (tpi): 24 Thread Size: 0.625 inches Nonpile-up Contact Arrangement: 2 two circuit, double break/double make, one position momentary single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc Thread Series Designator:	Body Diameter:
Body Length:  0.516 inches  Case Material:  Metal  Actuator Diameter:  0.375 inches  Actuator Height:  0.250 inches  Actuator Color:  Black single actuator  Maximum Voltage Rating In Volts:  30.0 dc  Inclosure Type:  Fully enclosed  Mounting Method:  Threaded bushing  Features Provided:  Rfi shielding  Thready Qty Per Inch (tpi):  24  Thread Size:  0.625 inches  Nonpile-up Contact Arrangement:  2 two circuit, double break/double make, one position momentary single switch unit  Contact Load Current Rating At Maximum Rated Voltage:  5.000 amperes resistive dc  Thread Series Designator:	0.500 inches
Body Length:  0.516 inches  Case Material: Metal  Actuator Diameter: 0.375 inches  Actuator Height: 0.250 inches  Actuator Color: Black single actuator  Maximum Voltage Rating In Volts: 30.0 dc  Inclosure Type: Fully enclosed  Mounting Method: Threaded bushing  Features Provided: Rfi shielding  Thready Qty Per Inch (tpi): 24  Thread Size: 0.625 inches  Nonpile-up Contact Arrangement: 2 two circuit, double break/double make, one position momentary single switch unit  Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc  Thread Series Designator:	Bushing Length:
Case Material: Metal Actuator Diameter: 0.375 inches Actuator Height: 0.250 inches Actuator Color: Black single actuator Maximum Voltage Rating In Volts: 30.0 dc Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Features Provided: Rfi shielding Thready Qty Per Inch (tpi): 24 Thread Size: 0.625 inches Nonpile-up Contact Arrangement: 2 two circuit, double break/double make, one position momentary single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc Thread Series Designator:	0.500 inches
Case Material: Metal Actuator Diameter: 0.375 inches Actuator Height: 0.250 inches Actuator Color: Black single actuator Maximum Voltage Rating In Volts: 30.0 dc Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Features Provided: Rfi shielding Thready Qty Per Inch (tpi): 24 Thread Size: 0.625 inches Nonpile-up Contact Arrangement: 2 two circuit, double break/double make, one position momentary single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc Thread Series Designator:	Body Length:
Metal Actuator Diameter: 0.375 inches Actuator Height: 0.250 inches Actuator Color: Black single actuator Maximum Voltage Rating In Volts: 30.0 dc Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Features Provided: Rfi shielding Thready Qty Per Inch (tpi): 24 Thread Size: 0.625 inches Nonpile-up Contact Arrangement: 2 two circuit, double break/double make, one position momentary single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc Thread Series Designator:	0.516 inches
Actuator Diameter:  0.375 inches  Actuator Height:  0.250 inches  Actuator Color:  Black single actuator  Maximum Voltage Rating In Volts:  30.0 dc  Inclosure Type:  Fully enclosed  Mounting Method:  Threaded bushing  Features Provided:  Rfi shielding  Thready Qty Per Inch (tpi):  24  Thread Size:  0.625 inches  Nonpile-up Contact Arrangement:  2 two circuit, double break/double make, one position momentary single switch unit  Contact Load Current Rating At Maximum Rated Voltage:  5.000 amperes resistive dc  Thread Series Designator:	Case Material:
0.375 inches Actuator Height: 0.250 inches Actuator Color: Black single actuator Maximum Voltage Rating In Volts: 30.0 dc Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Features Provided: Rfi shielding Thready Qty Per Inch (tpi): 24 Thread Size: 0.625 inches Nonpile-up Contact Arrangement: 2 two circuit, double break/double make, one position momentary single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc Thread Series Designator:	Metal
Actuator Height:  0.250 inches  Actuator Color:  Black single actuator  Maximum Voltage Rating In Volts:  30.0 dc  Inclosure Type:  Fully enclosed  Mounting Method:  Threaded bushing  Features Provided:  Rfi shielding  Thready Qty Per Inch (tpi):  24  Thread Size:  0.625 inches  Nonpile-up Contact Arrangement:  2 two circuit, double break/double make, one position momentary single switch unit  Contact Load Current Rating At Maximum Rated Voltage:  5.000 amperes resistive dc  Thread Series Designator:	Actuator Diameter:
O.250 inches  Actuator Color:  Black single actuator  Maximum Voltage Rating In Volts: 30.0 dc Inclosure Type:  Fully enclosed  Mounting Method:  Threaded bushing  Features Provided:  Rfi shielding  Thready Qty Per Inch (tpi): 24  Thread Size:  0.625 inches  Nonpile-up Contact Arrangement: 2 two circuit, double break/double make, one position momentary single switch unit  Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc  Thread Series Designator:	0.375 inches
Actuator Color: Black single actuator  Maximum Voltage Rating In Volts: 30.0 dc Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Features Provided: Rfi shielding Thready Qty Per Inch (tpi): 24 Thread Size: 0.625 inches Nonpile-up Contact Arrangement: 2 two circuit, double break/double make, one position momentary single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc Thread Series Designator:	Actuator Height:
Maximum Voltage Rating In Volts: 30.0 dc Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Features Provided: Rfi shielding Thready Qty Per Inch (tpi): 24 Thread Size: 0.625 inches Nonpile-up Contact Arrangement: 2 two circuit, double break/double make, one position momentary single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc Thread Series Designator:	0.250 inches
Maximum Voltage Rating In Volts:  30.0 dc Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Features Provided: Rfi shielding Thready Qty Per Inch (tpi): 24 Thread Size: 0.625 inches Nonpile-up Contact Arrangement: 2 two circuit, double break/double make, one position momentary single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc Thread Series Designator:	Actuator Color:
Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Features Provided: Rfi shielding Thready Qty Per Inch (tpi): 24 Thread Size: 0.625 inches Nonpile-up Contact Arrangement: 2 two circuit, double break/double make, one position momentary single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc Thread Series Designator:	Black single actuator
Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Features Provided: Rfi shielding Thready Qty Per Inch (tpi): 24 Thread Size: 0.625 inches Nonpile-up Contact Arrangement: 2 two circuit, double break/double make, one position momentary single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc Thread Series Designator:	Maximum Voltage Rating In Volts:
Fully enclosed  Mounting Method: Threaded bushing  Features Provided: Rfi shielding  Thready Qty Per Inch (tpi): 24  Thread Size: 0.625 inches  Nonpile-up Contact Arrangement: 2 two circuit, double break/double make, one position momentary single switch unit  Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc  Thread Series Designator:	30.0 dc
Mounting Method: Threaded bushing Features Provided: Rfi shielding Thready Qty Per Inch (tpi): 24 Thread Size: 0.625 inches Nonpile-up Contact Arrangement: 2 two circuit, double break/double make, one position momentary single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc Thread Series Designator:	Inclosure Type:
Threaded bushing  Features Provided: Rfi shielding  Thready Qty Per Inch (tpi): 24  Thread Size: 0.625 inches  Nonpile-up Contact Arrangement: 2 two circuit, double break/double make, one position momentary single switch unit  Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc  Thread Series Designator:	Fully enclosed
Features Provided: Rfi shielding Thready Qty Per Inch (tpi): 24 Thread Size: 0.625 inches Nonpile-up Contact Arrangement: 2 two circuit, double break/double make, one position momentary single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc Thread Series Designator:	Mounting Method:
Rfi shielding Thready Qty Per Inch (tpi): 24 Thread Size: 0.625 inches Nonpile-up Contact Arrangement: 2 two circuit, double break/double make, one position momentary single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc Thread Series Designator:	Threaded bushing
Thready Qty Per Inch (tpi): 24  Thread Size: 0.625 inches  Nonpile-up Contact Arrangement: 2 two circuit, double break/double make, one position momentary single switch unit  Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc  Thread Series Designator:	Features Provided:
Thread Size: 0.625 inches Nonpile-up Contact Arrangement: 2 two circuit, double break/double make, one position momentary single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc Thread Series Designator:	Rfi shielding
Thread Size:  0.625 inches  Nonpile-up Contact Arrangement:  2 two circuit, double break/double make, one position momentary single switch unit  Contact Load Current Rating At Maximum Rated Voltage:  5.000 amperes resistive dc  Thread Series Designator:	Thready Qty Per Inch (tpi):
0.625 inches  Nonpile-up Contact Arrangement:  2 two circuit, double break/double make, one position momentary single switch unit  Contact Load Current Rating At Maximum Rated Voltage:  5.000 amperes resistive dc  Thread Series Designator:	24
Nonpile-up Contact Arrangement:  2 two circuit, double break/double make, one position momentary single switch unit  Contact Load Current Rating At Maximum Rated Voltage:  5.000 amperes resistive dc  Thread Series Designator:	Thread Size:
2 two circuit, double break/double make, one position momentary single switch unit  Contact Load Current Rating At Maximum Rated Voltage:  5.000 amperes resistive dc  Thread Series Designator:	0.625 inches
Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc Thread Series Designator:	Nonpile-up Contact Arrangement:
5.000 amperes resistive dc  Thread Series Designator:	2 two circuit, double break/double make, one position momentary single switch unit
Thread Series Designator:	Contact Load Current Rating At Maximum Rated Voltage:
-	5.000 amperes resistive dc
Unef	Thread Series Designator:
	Unef

## NSN 5930-01-286-8042

Push Switch - Page 2 of 2



Terminal Type And Quantity:
8 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A053a0