NSN 5930-01-286-8915

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-286-8915

Body Style:			
Panel mounted			
Hazardous Locations/environmental Protection:			
Explosion proof and humidity resistant			
Overall Length:			
2.750 inches			
Overall Height:			
0.688 inches			
Overall Width:			
0.688 inches			
Body Width:			
0.688 inches			
Body Height:			
0.688 inches			
Case Material:			
Metal			
Actuator Length:			
0.620 inches			
Actuator Style:			
Rectangular			
Actuator Height:			
0.070 inches			
Actuator Width:			
0.620 inches			
Actuator Color:			
White single actuator			
Illuminated Actuator Color:			
White single actuator			
Actuator Inscription:			
Ext single actuator			
Maximum Voltage Rating In Volts:			
28.0 dc			
Mounting Surface To Terminal End Distance:			
2.680 inches			
Inclosure Type:			
Fully enclosed			
Mounting Method:			
Panel			
Nonpile-up Contact Arrangement:			
2 pole, double throw, one position momentary single switch unit			

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

NSN 5930-01-286-8915

Push Switch - Page 2 of 2



Precious	Material	And	Location:
----------	----------	-----	-----------

Contacts gold

Terminal Type And Quantity:

6 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A053a0