NSN 5930-01-286-8919

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-286-8919

| Body Style: | | | | |
|---|--|--|--|--|
| Panel mount | | | | |
| Hazardous Locations/environmental Protection: | | | | |
| Explosion proof and humidity resistant | | | | |
| Overall Length: | | | | |
| 0.688 inches | | | | |
| Overall Height: | | | | |
| 2.750 inches | | | | |
| Overall Width: | | | | |
| 0.688 inches | | | | |
| Body Length: | | | | |
| 0.688 inches | | | | |
| Body Width: | | | | |
| 0.688 inches | | | | |
| Body Height: | | | | |
| 2.680 inches | | | | |
| Case Material: | | | | |
| Metal | | | | |
| Actuator Length: | | | | |
| 0.620 inches | | | | |
| Actuator Style: | | | | |
| Rectangular | | | | |
| Actuator Height: | | | | |
| 0.070 inches | | | | |
| Actuator Width: | | | | |
| 0.620 inches | | | | |
| Actuator Color: | | | | |
| White single actuator | | | | |
| Illuminated Actuator Color: | | | | |
| White single actuator | | | | |
| Actuator Inscription: | | | | |
| Kwr46 2 single actuator | | | | |
| Maximum Voltage Rating In Volts: | | | | |
| 28.0 dc | | | | |
| Inclosure Type: | | | | |
| Fully enclosed | | | | |
| Mounting Method: | | | | |
| Panel | | | | |
| Nonpile-up Contact Arrangement: | | | | |
| 2 pole, double throw, one position momentary single switch unit | | | | |

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

NSN 5930-01-286-8919

Push Switch - Page 2 of 2



| Precious | Material | And | Location: |
|----------|----------|-----|-----------|
| | | | |

Contacts gold

Terminal Type And Quantity:

6 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0