NSN 5930-01-286-8922

Push Switch - Page 1 of 2

Body Style: Panel mount



View Online at https://aerobasegroup.com/nsn/5930-01-286-8922

Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
0.688 inches
Overall Height:
2.750 inches
Overall Width:
0.688 inches
Body Length:
0.688 inches
Body Width:
0.688 inches
Body Height:
2.680 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.070 inches
Actuator Width:
0.620 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
White single actuator
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
1.000 amperes resistive dc and 0.500 amperes inductive dc
Special Features:
No legend

NSN 5930-01-286-8922

Push Switch - Page 2 of 2



Precious Material And Location:
Contacts gold
Terminal Type And Quantity:
6 turret and 5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0