

View Online at <https://aerobasegroup.com/nsn/5930-01-286-8924>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Explosion proof and humidity resistant

**Overall Length:**

0.688 inches

**Overall Height:**

2.750 inches

**Overall Width:**

0.688 inches

**Body Length:**

0.688 inches

**Body Width:**

0.688 inches

**Body Height:**

2.680 inches

**Case Material:**

Metal

**Actuator Length:**

0.620 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.070 inches

**Actuator Width:**

0.620 inches

**Actuator Color:**

White single actuator

**Illuminated Actuator Color:**

White single actuator

**Actuator Inscription:**

Msg proc single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 0.500 amperes inductive dc

**Precious Material And Location:**

Contacts gold

**Terminal Type And Quantity:**

6 turret and 5 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0