## NSN 5930-01-286-8926

Push Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-01-286-8926



#### **Body Style:**

Panel mount

#### Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

#### **Overall Length:**

0.688 inches

#### **Overall Height:**

2.750 inches

#### **Overall Width:**

0.688 inches

- **Body Length:**
- 0.688 inches

Body Width:

#### 0.688 inches

Body Height:

## 2.680 inches

Case Material:

Metal

Actuator Length:

0.620 inches

#### **Actuator Style:**

Rectangular

#### Actuator Height:

0.070 inches

#### Actuator Width:

0.620 inches

#### Actuator Color:

White single actuator

#### Illuminated Actuator Color:

White single actuator

#### **Actuator Inscription:**

Ext single actuator

#### Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

### **Mounting Method:**

Panel

#### Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

#### Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

# NSN 5930-01-286-8926

Push Switch - Page 2 of 2



**Precious Material And Location:** 

Contacts gold

## Terminal Type And Quantity:

6 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0