NSN 5930-01-286-8927

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-286-8927

| Body Style: |
|---|
| Panel mount |
| Hazardous Locations/environmental Protection: |
| Explosion proof and humidity resistant |
| Overall Length: |
| 0.688 inches |
| Overall Height: |
| 2.750 inches |
| Overall Width: |
| 0.688 inches |
| Body Length: |
| 0.688 inches |
| Body Width: |
| 0.688 inches |
| Body Height: |
| 2.680 inches |
| Case Material: |
| Metal |
| Actuator Length: |
| 0.620 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.070 inches |
| Actuator Width: |
| 0.620 inches |
| Actuator Color: |
| White single actuator |
| Illuminated Actuator Color: |
| White single actuator |
| Actuator Inscription: |
| VIf proc 1 single actuator |
| Maximum Voltage Rating In Volts: |
| 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |

1.000 amperes resistive dc and 0.500 amperes inductive dc

NSN 5930-01-286-8927

Push Switch - Page 2 of 2



| Precious Material And Location: |
|--|
| Contacts gold |
| Terminal Type And Quantity: |
| 6 turret and 5 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

Demilitarization:

No

Fiig:

A053a0