# NSN 5930-01-286-9049

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-286-9049

## **Thread Class:**

2a single mounting facility

### **Thread Length:**

0.469 inches single mounting facility

## **Overall Length:**

4.375 inches

## **Overall Diameter:**

2.000 inches

## Individual Section Quantity:

6

### Switch Contact Basic Design:

Nonpile-up symmetrical

## Pole Quantity:

1 each section periphery

## Throw Quantity:

7 each section periphery

## Mounting Method:

Threaded bushing single mounting facility

### Features Provided:

Actuator knob

## Thready Qty Per Inch (tpi):

32 single mounting facility

### Thread Size:

0.469 inches single mounting facility

### **Contact Voltage Rating In Volts:**

600.0 highest ac voltage rating at sea level

## Switch Actuator Indexing Position Quantity:

8 single actuator

## **Terminal Type:**

Screw

### **Contact Switching Action:**

Breaks before makes each section periphery

### **Switch Actuator Positioning Increment:**

45.0 degrees single actuator

### Switch Actuator Stop Device Type:

Adjustable stop single actuator

## **Contact Load Current Rating:**

5.0 amperes resistive load lowest dc voltage rating at sea level

## **Precious Material And Location:**

Rotor and contact surfaces silver

## **Precious Material:**

Silver

# NSN 5930-01-286-9049

Rotary Switch - Page 2 of 2

## Style Designator:

Tap, circular, bushing mount

## Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A052b0

