

View Online at <https://aerobasegroup.com/nsn/5930-01-286-9050>

Thread Class:

2b single mounting facility

Overall Length:

6.875 inches

Overall Height:

2.910 inches

Overall Width:

2.810 inches

Individual Section Quantity:

4

Longest Horizontal Distance Between Mounting Centers:

2.000 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.180 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

500.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Switch Actuator Indexing Position Quantity:

8 single actuator

Terminal Type:

Screw

Contact Switching Action:

Makes before breaks 1st section periphery

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load highest ac voltage rating at sea level

Special Features:

Altered iaw dwg 401-5583119

Precious Material And Location:

Rotor and stator surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0