## NSN 5930-01-286-9915

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-286-9915

Body Style:				
Panel mounted				
Hazardous Locations/environmental Protection:				
Explosion proof and humidity resistant				
Overall Length:				
2.750 inches				
Overall Height:				
0.688 inches				
Overall Width:				
0.688 inches				
Body Width:				
0.688 inches				
Body Height:				
0.699 inches				
Case Material:				
Metal				
Actuator Length:				
0.620 inches				
Actuator Style:				
Rectangular				
Actuator Height:				
0.070 inches				
Actuator Width:				
0.620 inches				
Actuator Color:				
White single actuator				
Illuminated Actuator Color:				
White single actuator				
Actuator Inscription:				
Kwr46 1 single actuator				
Maximum Voltage Rating In Volts:				
28.0 dc				
Mounting Surface To Terminal End Distance:				
2.680 inches				
Inclosure Type:				
Fully enclosed				
Mounting Method:				
Panel				
Nonpile-up Contact Arrangement:				
2 pole, double throw, one position momentary single switch unit				

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

## NSN 5930-01-286-9915

Push Switch - Page 2 of 2



Precious N	Material A	And I	Location:
------------	------------	-------	-----------

Contacts gold

**Terminal Type And Quantity:** 

6 turret and 5 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0