NSN 5930-01-286-9917

Push Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-01-286-9917



Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

Overall Length:

2.751 inches

Overall Height:

0.688 inches

Overall Width:

0.688 inches

- **Body Width:**
- 0.688 inches

Body Height:

0.688 inches

Case Material:

Metal

Actuator Length:

J

0.620 inches

Actuator Style:

Rectangular

Actuator Height:

0.070 inches

Actuator Width:

0.620 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

White single actuator

Actuator Inscription:

Kwr46 2/proc single actuator

Maximum Voltage Rating In Volts:

28.0 dc

Mounting Surface To Terminal End Distance:

2.680 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

NSN 5930-01-286-9917

Push Switch - Page 2 of 2



Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

6 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0