## NSN 5930-01-286-9921

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-286-9921

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
2.751 inches
Overall Height:
0.688 inches
Overall Width:
0.688 inches
Body Width:
0.688 inches
Body Height:
0.688 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.070 inches
Actuator Width:
0.620 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
White single actuator
Actuator Inscription:
Kg36/ss1xs single actuator
Maximum Voltage Rating In Volts:
28.0 dc
Mounting Surface To Terminal End Distance:
2.680 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:** 

1.000 amperes resistive dc and 0.500 amperes inductive dc

## NSN 5930-01-286-9921

Push Switch - Page 2 of 2



recious	s iviateria	ı Ana	Location:

Contacts gold

**Terminal Type And Quantity:** 

6 turret and 5 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0