

View Online at <https://aerobasegroup.com/nsn/5930-01-287-0014>

Hazardous Locations/environmental Protection:

Corrosion resistant

Overall Length:

3.500 inches

Overall Height:

6.600 inches

Overall Width:

2.850 inches

Body Height:

3.500 inches

Unthreaded Mounting Hole Diameter:

0.265 inches

Capillary Tube Length:

72.0 inches

Bulb Length:

4.500 inches

Bulb Diameter:

0.375 inches

Longest Horizontal Distance Between Mounting Centers:

2.720 inches

Longest Vertical Distance Between Mounting Centers:

2.720 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Operating Temperature Rating:

Between -40.0 degrees fahrenheit and 180.0 degrees fahrenheit

Mounting Method:

Base and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

5.0 amperes resistive load second voltage and 3.0 amperes inductive load second voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+60.00/+205.00 actuation point degrees fahrenheit and +40.00/+200.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

Internal actuation point hex nut and internal deactuation point hex nut

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0