NSN 5930-01-287-2341

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-287-2341

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
0.688 inches
Overall Height:
2.750 inches
Overall Width:
0.688 inches
Body Length:
0.688 inches
Body Width:
0.688 inches
Body Height:
2.680 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.070 inches
Actuator Width:
0.620 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
White single actuator
Actuator Inscription:
Kwr 46 1 single actuator
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Lond Comment Poting At Maximum Poted Voltage

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

NSN 5930-01-287-2341

Push Switch - Page 2 of 2



Full display lens with two line inscription

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

6 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0