

View Online at <https://aerobasegroup.com/nsn/5930-01-287-3602>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Corrosion resistant

Overall Length:

11.000 inches

Overall Height:

4.000 inches

Overall Width:

4.500 inches

Shaft Diameter:

0.500 inches single actuator

Shaft Length:

4.125 inches single actuator

Individual Section Quantity:

3

Mounting Method:

Base single mounting facility and threaded hole single mounting facility

Features Provided:

Cam actuated and spring return

Thready Qty Per Inch (tpi):

20 single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

480.0 highest ac voltage rating at sea level

Switch Actuator Momentary Position:

Clockwise single actuator and counterclockwise single actuator

Cam Actuated Switch Contact Arrangement:

1 pole, double throw, one position momentary each switch each section in-line

Switch Actuator Indexing Position Quantity:

7 single actuator

Shaft Type:

Round w/through hole single actuator

Terminal Type:

Screw

Switch Actuator Positioning Increment:

15.0 degrees single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load lowest dc voltage rating at sea level

Special Features:

Rotation to actuate 3rd speed is clockwise

Style Designator:

In-line, cam actuated

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0