

View Online at <https://aerobasegroup.com/nsn/5930-01-287-3602>

**Thread Class:**

2b single mounting facility

**Hazardous Locations/environmental Protection:**

Corrosion resistant

**Overall Length:**

11.000 inches

**Overall Height:**

4.000 inches

**Overall Width:**

4.500 inches

**Shaft Diameter:**

0.500 inches single actuator

**Shaft Length:**

4.125 inches single actuator

**Individual Section Quantity:**

3

**Mounting Method:**

Base single mounting facility and threaded hole single mounting facility

**Features Provided:**

Cam actuated and spring return

**Thready Qty Per Inch (tpi):**

20 single mounting facility

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

480.0 highest ac voltage rating at sea level

**Switch Actuator Momentary Position:**

Clockwise single actuator and counterclockwise single actuator

**Cam Actuated Switch Contact Arrangement:**

1 pole, double throw, one position momentary each switch each section in-line

**Switch Actuator Indexing Position Quantity:**

7 single actuator

**Shaft Type:**

Round w/through hole single actuator

**Terminal Type:**

Screw

**Switch Actuator Positioning Increment:**

15.0 degrees single actuator

**Contact Load Current Rating:**

500.0 milliamperes resistive load lowest dc voltage rating at sea level

**Special Features:**

Rotation to actuate 3rd speed is clockwise

**Style Designator:**

In-line, cam actuated

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0