NSN 5930-01-287-3602

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-287-3602 **Thread Class:** 2b single mounting facility **Hazardous Locations/environmental Protection:** Corrosion resistant **Overall Length:** 11.000 inches **Overall Height:** 4.000 inches **Overall Width:** 4.500 inches **Shaft Diameter:** 0.500 inches single actuator Shaft Length: 4.125 inches single actuator **Individual Section Quantity:**

_

Mounting Method:

Base single mounting facility and threaded hole single mounting facility

Features Provided:

Cam actuated and spring return

Thready Qty Per Inch (tpi):

20 single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

480.0 highest ac voltage rating at sea level

Switch Actuator Momentary Position:

Clockwise single actuator and counterclockwise single actuator

Cam Actuated Switch Contact Arrangement:

1 pole, double throw, one position momentary each switch each section in-line

Switch Actuator Indexing Position Quantity:

7 single actuator

Shaft Type:

Round w/through hole single actuator

Terminal Type:

Screw

Switch Actuator Positioning Increment:

15.0 degrees single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load lowest dc voltage rating at sea level

Special Features:

Rotation to actuate 3rd speed is clockwise

NSN 5930-01-287-3602

Rotary Switch - Page 2 of 2



Styl			

In-line, cam actuated

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0