# NSN 5930-01-287-3602

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-287-3602 **Thread Class:** 2b single mounting facility **Hazardous Locations/environmental Protection:** Corrosion resistant **Overall Length:** 11.000 inches **Overall Height:** 4.000 inches **Overall Width:** 4.500 inches **Shaft Diameter:** 0.500 inches single actuator Shaft Length: 4.125 inches single actuator **Individual Section Quantity:** 

\_

#### **Mounting Method:**

Base single mounting facility and threaded hole single mounting facility

#### **Features Provided:**

Cam actuated and spring return

# Thready Qty Per Inch (tpi):

20 single mounting facility

#### **Thread Size:**

0.250 inches single mounting facility

# **Contact Voltage Rating In Volts:**

480.0 highest ac voltage rating at sea level

#### **Switch Actuator Momentary Position:**

Clockwise single actuator and counterclockwise single actuator

#### **Cam Actuated Switch Contact Arrangement:**

1 pole, double throw, one position momentary each switch each section in-line

## **Switch Actuator Indexing Position Quantity:**

7 single actuator

#### **Shaft Type:**

Round w/through hole single actuator

#### **Terminal Type:**

Screw

## **Switch Actuator Positioning Increment:**

15.0 degrees single actuator

# **Contact Load Current Rating:**

500.0 milliamperes resistive load lowest dc voltage rating at sea level

#### **Special Features:**

Rotation to actuate 3rd speed is clockwise

# NSN 5930-01-287-3602

Rotary Switch - Page 2 of 2



Styl			

In-line, cam actuated

**Thread Series Designator:** 

Unc single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0