

View Online at <https://aerobasegroup.com/nsn/5930-01-287-6698>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Moisture resistant

**Overall Length:**

Between 1.910 inches and 1.970 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.990 inches and 1.010 inches

**Overall Height:**

0.984 inches

**Overall Width:**

0.750 inches

**Body Length:**

Between 1.910 inches and 1.970 inches

**Body Width:**

Between 0.677 inches and 0.697 inches

**Body Height:**

0.984 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.139 inches and 0.143 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.160 inches

**Actuator Height:**

0.094 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

2310-01-111-2274

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

15.0 ounces

**Actuator Movement:**

Between 0.090 pretravel inches and 0.005 overtravel inches and 0.005 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive dc and 1.000 amperes inductive dc and 1.500 amperes lamp dc and 15.000 amperes resistive ac and 15.000 amperes inductive ac and 1.500 amperes lamp ac

**Precious Material And Location:**

Contacts silver

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0