

View Online at <https://aerobasegroup.com/nsn/5930-01-287-6698>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Moisture resistant

Overall Length:

Between 1.910 inches and 1.970 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.990 inches and 1.010 inches

Overall Height:

0.984 inches

Overall Width:

0.750 inches

Body Length:

Between 1.910 inches and 1.970 inches

Body Width:

Between 0.677 inches and 0.697 inches

Body Height:

0.984 inches

Unthreaded Mounting Hole Diameter:

Between 0.139 inches and 0.143 inches

Actuator Style:

Round

Actuator Diameter:

0.160 inches

Actuator Height:

0.094 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

2310-01-111-2274

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

15.0 ounces

Actuator Movement:

Between 0.090 pretravel inches and 0.005 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.000 amperes inductive dc and 1.500 amperes lamp dc and 15.000 amperes resistive ac and 15.000 amperes inductive ac and 1.500 amperes lamp ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0