

View Online at <https://aerobasegroup.com/nsn/5930-01-288-0168>

Inside Diameter:

0.500 inches single connection

Hazardous Locations/environmental Protection:

Weathertight and corrosion resistant

Overall Length:

5.470 inches

Overall Height:

6.360 inches

Overall Width:

2.320 inches

Body Height:

4.480 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Distance Between Mounting Facility Centers:

4.500 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between 0.0 degrees fahrenheit and 400.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Decrease

Proof Pressure:

2500.00 pounds per square inch

Thread Size:

0.500 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

+25.00/+275.00 actuation point pounds per square inch

Contact Adjustment Type:

Internal actuation point hex nut with scale

Contact Stimulus Rating:

160.00 actuation point pounds per square inch

Contact Voltage Rating In Volts:

480.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Nptf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0