

View Online at <https://aerobasegroup.com/nsn/5930-01-288-0174>

Body Style:

Panel mount

Overall Length:

1.200 inches

Overall Height:

3.102 inches

Overall Width:

0.960 inches

Body Length:

1.090 inches

Body Width:

0.850 inches

Body Height:

2.962 inches

Actuator Length:

1.040 inches

Actuator Style:

Rectangular

Actuator Height:

0.140 inches

Actuator Width:

0.800 inches

Actuator Color:

White single actuator and white single actuator

Illuminated Actuator Color:

White single actuator and white single actuator

Illuminated Actuator Color Sequence:

Upper half of actuator white, lower half of actuator white

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Uninclosed

Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

Special Features:

High impact shock; horizontal split lens

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

5 tab, solder lug and 12 turret

Specification Data:

81349-mil-s-22885/87 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0