

View Online at <https://aerobasegroup.com/nsn/5930-01-288-3834>

Hazardous Locations/environmental Protection:

Moisture resistant

Overall Length:

4.220 inches

Overall Height:

5.450 inches

Overall Width:

2.230 inches

Body Height:

3.125 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Distance Between Mounting Facility Centers:

2.750 inches

Capillary Tube Length:

72.0 inches

Bulb Length:

4.410 inches

Bulb Diameter:

0.380 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Flange and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

400.0 milliamperes resistive load second voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

+40.00/+225.00 actuation point degrees fahrenheit

Contact Adjustment Type:

Internal actuation point hex nut with scale

Contact Stimulus Rating:

160.00 actuation point degrees fahrenheit

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0