

View Online at <https://aerobasegroup.com/nsn/5930-01-288-5638>

Body Style:

Bushing mount

Overall Length:

0.510 inches

Overall Height:

1.187 inches

Overall Width:

0.575 inches

Bushing Length:

0.270 inches

Body Length:

0.510 inches

Body Width:

0.465 inches

Body Height:

0.375 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

0.105 inches

Actuator Height:

0.287 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Actuator Position-locking Relationship:

Up position locked in and down position locked in and center position locked out

Maximum Voltage Rating In Volts:

125.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Nonpile-up Contact Arrangement:

6 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac and 1.000 amperes lamp ac

Special Features:

Pc board mounted; bushing unthreaded

Test Data Document:

81349-mil-s-83731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical" "average" "" etc.)

Terminal Type And Quantity:

6 pin

Specification Data:

81349-mil-s-83731/16 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0