

View Online at <https://aerobasegroup.com/nsn/5930-01-288-5639>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.375 inches

**Body Length:**

0.780 inches

**Body Width:**

0.250 inches

**Body Height:**

0.370 inches

**Unthreaded Mounting Hole Diameter:**

0.089 inches

**Actuator Length:**

0.092 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.064 inches

**Actuator Width:**

0.122 inches

**Actuator Free Position Height:**

0.360 inches

**Maximum Voltage Rating In Volts:**

250.0 ac

**End Application:**

1730-01-118-5451

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

1.0 ounces

**Switch Actuating Force:**

5.0 ounces

**Actuator Movement:**

0.004 differential inches and 0.030 pretravel inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive ac

**Precious Material And Location:**

Contacts silver

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A053a0