## NSN 5930-01-288-5639

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-288-5639

Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Body Length:
0.780 inches
Body Width:
0.250 inches
Body Height:
0.370 inches
Unthreaded Mounting Hole Diameter:
0.089 inches
Actuator Length:
0.092 inches
Actuator Style:
Rectangular
Actuator Height:
0.064 inches
Actuator Width:
0.122 inches
Actuator Free Position Height:
0.360 inches
Maximum Voltage Rating In Volts:
250.0 ac
End Application:
1730-01-118-5451
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
1.0 ounces
Switch Actuating Force:
5.0 ounces
Actuator Movement:
0.004 differential inches and 0.030 pretravel inches
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive ac

**Precious Material And Location:** 

i recious material Ana Et

Contacts silver

## NSN 5930-01-288-5639

Sensitive Switch - Page 2 of 2



Terminal Type A	nd Quantity:
-----------------	--------------

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0