

View Online at <https://aerobasegroup.com/nsn/5930-01-288-5640>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Moisture resistant

**Overall Length:**

Between 1.070 inches and 1.090 inches

**Overall Height:**

3.130 inches

**Overall Width:**

Between 1.070 inches and 1.090 inches

**Body Length:**

0.688 inches

**Body Width:**

Between 0.740 inches and 0.760 inches

**Body Height:**

2.850 inches

**Case Material:**

Metal

**Actuator Length:**

Between 0.802 inches and 0.822 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

Between 0.260 inches and 0.280 inches

**Actuator Width:**

Between 0.802 inches and 0.822 inches

**Actuator Color:**

White single actuator

**Illuminated Actuator Color:**

White single actuator

**Actuator Inscription:**

Off single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 0.500 amperes inductive dc

**Special Features:**

Full display lens

**Precious Material And Location:**

Contacts gold

**Terminal Type And Quantity:**

3 turret and 5 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0