NSN 5930-01-288-5642

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-288-5642

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Moisture resistant

Overall Length:

Between 1.070 inches and 1.090 inches

Overall Height:

3.130 inches

Overall Width:

Between 1.070 inches and 1.090 inches

Body Length:

0.688 inches

Body Width:

Between 0.740 inches and 0.760 inches

Body Height:

2.850 inches

Case Material:

Metal

Actuator Length:

Between 0.802 inches and 0.822 inches

Actuator Style:

Rectangular

Actuator Height:

Between 0.260 inches and 0.280 inches

Actuator Width:

Between 0.802 inches and 0.822 inches

Actuator Color:

White single actuator and white single actuator

Illuminated Actuator Color:

Amber single actuator and red single actuator

Actuator Inscription:

Repeat mode/repeat single actuator

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

NSN 5930-01-288-5642

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

Special Features:

Horizontal split display

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

3 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0