# NSN 5930-01-288-6670

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-288-6670

# Thread Class:

2a single mounting facility

# Thread Length:

0.437 inches single mounting facility

# Hazardous Locations/environmental Protection:

Explosion proof

#### **Overall Length:**

2.180 inches

#### First Flat Length:

0.250 inches single actuator

#### Flat Height:

0.216 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.437 inches single actuator

**Overall Diameter:** 

1.430 inches

### Nonturn Device Radius:

0.375 inches at 3: 00 o'clock

# Individual Section Quantity:

3

#### Nonturn Device Type:

Tab at 3: 00 o'clock

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### Pole Quantity:

3 each section front

#### Throw Quantity:

4 each section rear

#### **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

#### Contact Voltage Rating In Volts:

28.0 dc at sea level

#### **Rotor Through Connection Quantity:**

3 each section

### Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

# NSN 5930-01-288-6670

Rotary Switch - Page 2 of 2



#### **Terminal Type:**

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

350.0 milliamperes resistive load ac at sea level

#### Style Designator:

Tap, circular, bushing mount

#### **Test Data Document:**

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Thread Series Designator:**

Unef single mounting facility

#### **Specification Data:**

81349-mil-s-3786/28 government specification

Shelf Life:

N/a

Unit Of Measure:

--

# Demilitarization:

No

#### Fiig:

A052b0