### NSN 5930-01-288-6675

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-288-6675

**Body Style:** 

Panel mount

**Overall Length:** 

1.200 inches

**Overall Height:** 

3.102 inches

**Overall Width:** 

0.960 inches

**Body Length:** 

1.090 inches

**Body Width:** 

0.850 inches

Body Height:

2.962 inches

Actuator Length:

### 1.040 inches

Actuator Style:

Rectangular

Actuator Height:

0.140 inches

Actuator Width:

0.800 inches

Actuator Color:

White single actuator

**Illuminated Actuator Color:** 

White single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Uninclosed

**Mounting Method:** 

Panel

#### Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

#### Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

**Special Features:** 

High impact shock

**Test Data Document:** 

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

## NSN 5930-01-288-6675

Push Switch - Page 2 of 2



**Specification Data:** 

81349-mil-s-22885/87 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0