## NSN 5930-01-288-6676

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-288-6676

| Body Style:                                                     |
|-----------------------------------------------------------------|
| Panel mount                                                     |
| Hazardous Locations/environmental Protection:                   |
| Moisture resistant                                              |
| Overall Length:                                                 |
| Between 1.070 inches and 1.090 inches                           |
| Overall Height:                                                 |
| 3.130 inches                                                    |
| Overall Width:                                                  |
| Between 1.070 inches and 1.090 inches                           |
| Body Length:                                                    |
| 0.688 inches                                                    |
| Body Width:                                                     |
| Between 0.740 inches and 0.760 inches                           |
| Body Height:                                                    |
| 2.850 inches                                                    |
| Case Material:                                                  |
| Metal                                                           |
| Actuator Length:                                                |
| Between 0.802 inches and 0.822 inches                           |
| Actuator Style:                                                 |
| Rectangular                                                     |
| Actuator Height:                                                |
| Between 0.260 inches and 0.280 inches                           |
| Actuator Width:                                                 |
| Between 0.802 inches and 0.822 inches                           |
| Actuator Color:                                                 |
| White single actuator                                           |
| Illuminated Actuator Color:                                     |
| Blue single actuator                                            |
| Actuator Inscription:                                           |
| Self test single actuator                                       |
| Maximum Voltage Rating In Volts:                                |
| 28.0 dc                                                         |
| Inclosure Type:                                                 |
| Fully enclosed                                                  |
| Mounting Method:                                                |
| Panel                                                           |
| Features Provided:                                              |
| Actuator seal                                                   |
| Nonpile-up Contact Arrangement:                                 |
| 1 pole, double throw, one position momentary single switch unit |

## NSN 5930-01-288-6676

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 0.500 amperes inductive dc

**Special Features:** 

Full display lens

**Precious Material And Location:** 

Contacts gold

**Terminal Type And Quantity:** 

3 turret and 5 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0