NSN 5930-01-288-6676

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-288-6676

Body Style: Panel mount Hazardous Locations/environmental Protection: Moisture resistant **Overall Length:** Between 1.070 inches and 1.090 inches **Overall Height:** 3.130 inches **Overall Width:** Between 1.070 inches and 1.090 inches **Body Length:** 0.688 inches **Body Width:** Between 0.740 inches and 0.760 inches **Body Height:** 2.850 inches **Case Material:** Metal Actuator Length: Between 0.802 inches and 0.822 inches **Actuator Style:** Rectangular **Actuator Height:** Between 0.260 inches and 0.280 inches Actuator Width: Between 0.802 inches and 0.822 inches **Actuator Color:** White single actuator **Illuminated Actuator Color:** Blue single actuator **Actuator Inscription:** Self test single actuator Maximum Voltage Rating In Volts: 28.0 dc Inclosure Type: Fully enclosed **Mounting Method:** Panel **Features Provided:** Actuator seal **Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

NSN 5930-01-288-6676

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

Special Features:

Full display lens

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

3 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0