NSN 5930-01-289-4887

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-289-4887

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
3.900 inches
Overall Height:
3.565 inches
Overall Width:
2.130 inches
Actuator Style:
Flexible
Actuator Diameter:
0.130 inches
Actuator Height:
6.000 inches
Housing Height:
1.580 inches
Housing Length:
3.390 inches
Housing Width:
1.020 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.950 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.220 inches
Maximum Voltage Rating In Volts:
600.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Actuating Force:
Between 3.0 ounces and 7.0 ounces
Actuator Movement:
Between 0.718 pretravel inches and 0.838 overtravel inches and 0.229 differential inches

Terminal Type And Quantity:

Contact Load Current Rating At Maximum Rated Voltage: 250.000 milliamperes resistive dc and 2.000 amperes resistive ac

3 screw

NSN 5930-01-289-4887

Sensitive Switch - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0