

View Online at <https://aerobasegroup.com/nsn/5930-01-289-7378>

Body Style:

Bushing mount

Overall Length:

Between 1.010 inches and 1.090 inches

Overall Height:

Between 1.820 inches and 2.040 inches

Overall Width:

Between 0.770 inches and 0.850 inches

Bushing Length:

Between 0.360 inches and 0.400 inches

Body Length:

Between 1.010 inches and 1.090 inches

Body Width:

Between 0.770 inches and 0.850 inches

Body Height:

Between 0.800 inches and 0.840 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.100 inches and 0.140 inches

Actuator Height:

Between 0.580 inches and 0.680 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained and left position momentary and right position momentary

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 four way single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0