

View Online at <https://aerobasegroup.com/nsn/5930-01-290-0110>

Inside Diameter:

0.250 inches single connection

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

3.500 inches

Overall Height:

7.180 inches

Overall Width:

2.580 inches

Body Height:

3.500 inches

Unthreaded Mounting Hole Diameter:

0.270 inches

Longest Horizontal Distance Between Mounting Centers:

2.720 inches

Longest Vertical Distance Between Mounting Centers:

2.720 inches

Pressure Switch Type:

Differential

Mounting Method:

Base and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Proof Pressure:

1300.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, both positions maintained

Terminal Type:

Screw

Contact Load Current Rating:

6.0 amperes inductive load first voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+14.70/+664.70 actuation point pounds per square inch absolute and +14.70/+664.70 deactuation point pounds per square inch absolute

Contact Adjustment Type:

External actuation point screw and external deactuation point screw

Contact Voltage Rating In Volts:

600.0 ac at sea level fourth voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0